

SUN CNC華勝自動化有限公司 台中市豐原區社皮里豐原大道一段428巷22弄90號

http://www.sun-cnc.com.tw E-mail:sn@sun-cnc.com.tw TEL:04-25337731

FAX:04-25349224

1300W


SGDV-120A01A




SGMGV-13ADA6S 無煞車


SGMGV-13ADA6E 有煞車


> T-N 曲線



>驅動器尺寸







_________大致質量: 2.4kg

伺服馬達型號 SGM	03A	05A	09A	13A	20A	30A	44A	55A	75A	1AA	1EA	
額定輸出*1	kW	0.3	0.45	0.85	1.3	1.8	2.9 2.4* ²	4.4	5.5	7.5	11	15
額定轉矩*1	N·m	1.96	2.86	5.39	8.34	11.5	18.6 15.1*2	28.4	35.0	48.0	70.0	95.4
瞬時最大轉矩*1	N·m	5.88	8.92	13.8	23.3	28.7	45.1	71.1	87.6	119	175	224
額定電流*1	Arms	2.8	3.8	6.9	10.7	16.7	23.8 19.6*2	l 32.8 l		54.7	58.6	78
瞬時最大電流*1	Arms	8	11	17	28	42	56	84	110	130	140	170
額定轉速*1	min-1		1500									
最高轉速*1	min-1						2000					
轉矩常數	N·m/Arms	0.776	0.854	0.859	0.891	0.748	0.848	0.934	0.871	0.957	1.32	1.37
轉子轉動慣量	×10 ⁻⁴ kg⋅m ²	2.48 (2.73)	3.33 (3.58)	13.9 (16)	19.9 (22)	26 (28.1)	46 (54.5)	67.5 (76.0)	89.0 (97.5)	125 (134)	242 (261)	303 (341)
額定功率變化率 *1	kW/s	15.5 (14.1)	24.6 (22.8)	20.9	35.0 (31.6)	50.9 (47.1)	75.2 (63.5)	119 (106)	138 (126)	184 (172)	202 (188)	300 (283)
額定角加速度*1	rad/s ²	7900 (7180)	8590 (7990)	3880 (3370)	4190 (3790)	4420 (4090)	4040 (3410)	4210 (3740)	3930 (3590)	3840 (3580)	2890 (2680)	3150 (2960)
配套伺服驅動器	SGDV-000	3R8A	3R8A	7R6A	120A	180A	330A 200A*2	330A	470A	550A	590A	780A



SUN CNC華勝自動化有限公司 台中市豐原區社皮里豐原大道一段428巷22弄90號


http://www.sun-cnc.com.tw E-mail:sn@sun-cnc.com.tw TEL:04-25337731

FAX:04-25349224


1300W 無煞車

>外觀尺寸

(2)850W ~ 7.5kW



型號 SGMGV-	L	LL	LM	LR	KB1	KB2	ΙE	KL1	法蘭面尺寸							軸端凡	大致 質量	
SGIVIGV-									LA	LB	LC	LE	LG	LH	LZ	S	Q	kg
09□□A21	195	137	101	58	83	125	_	104	145	110 _{-0.035}	130	6	12	165	9	19 ⁰ _{-0.013}	40	5.5
13□□A21	211	153	117	58	99	141	_	104	145	110 ⁰ -0.035	130	6	12	165	9	22 _{-0.013}	40	7.1
20□□A21	229	171	135	58	117	159	-	104	145	110 _{-0.035}	130	6	12	165	9	24 ⁰ -0.013	40	8.6
30□□A21	239	160	124	79	108	148	-	134	200	114.3 ⁰ _{-0.025}	180	3.2	18	230	13.5	35 ^{+0.01}	76	13.5
44□□A21	263	184	148	79	132	172	-	134	200	114.3 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	180	3.2	18	230	13.5	35 ^{+0.01}	76	17.5
55□□A21	334	221	185	113	163	209	123	144	200	114.3 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	180	3.2	18	230	13.5	42 -0.016	110	21.5
75□□A21	380	267	231	113	209	255	123	144	200	114.3 ⁰ _{-0.025}	180	3.2	18	230	13.5	42 -0.016	110	29.5



型號 SGMGV-	L	7	LL	LL	LL	LM	LR	KB1	KB2	KB3	ΙE	KL1	KL3	法蘭面尺寸							軸端月	大致 質量									
361016 7											LA	LB	LC	LE	LG	LH	LZ	S	Q	kg											
09□□A2□	231	173	137	58	83	161	115	-	104	80	145	110 _{-0.035}	130	6	12	165	9	19 _{-0.013}	40	7.5											
13□□A2□	247	189	153	58	99	177	131	-	104	80	145	110_0.035	130	6	12	165	9	22-0.013	40	9.0											
20□□A2□	265	207	171	58	117	195	149		104	80	145	110-0.035	130	6	12	165	9	24-0.013	40	11.0											
30□□A2□	287	208	172	79	108	196	148	_	134	110	200	114.3 -0.025	180	3.2	18	230	13.5	35 ^{+0.01}	76	19.5											
44□□A2□	311	232	196	79	132	220	172	-	134	110	200	114.3 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	180	3.2	18	230	13.5	35 ^{+0.01}	76	23.5											
55□□A2□	378	265	229	113	163	253	205	123	144	110	200	114.3 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	180	3.2	18	230	13.5	42-0.016	110	27.5											
75□□A2□	424	311	275	113	209	299	251	123	144	110	200	114.3-0.025	180	3.2	18	230	13.5	42-0.016	110	35											



SUN CNC華勝自動化有限公司 台中市豐原區社皮里豐原大道一段428巷22弄90號

http://www.sun-cnc.com.tw E-mail:sn@sun-cnc.com.tw TEL:04-25337731

FAX:04-25349224

鍵槽尺寸

料亦永固	伺服馬達型號 SGMGV-										
軸端詳圖	03	05	09	13	20	30/44	55/75	1A	1E		
符號: 2(直軸、不帶鍵槽)											
LR LR	LR	37	40	58	58	58	79	113	116	116	
	Q	25	30	40	40	40	76	110	110	110	
øs øs	S	14 -0.011	16 -0.011	19 -0.013	22 ⁰ _{-0.013}	24 -0.013	35 ^{+0.01}	42_0.016	42_0.016	55 ^{+0.030} _{+0.011}	
符號:6(直軸、帶鍵槽、帶螺孔)											
	LR	37	40	58	58	58	79	113	116	116	
. LR .	Q	25	30	40	40	40	76	110	110	110	
	QK	15	20	25	25	25	60	90	90	90	
Q QK U P	S	14 -0.011	16 -0.011	19 -0.013	22 -0.013	24 -0.013	35 ^{+0.01}	42_0.016	42_0.016	55 ^{+0.030} _{+0.011}	
	W	5	5	5	6	8	10	12	12	16	
	Т	5	5	5	6	7	8	8	8	10	
	U	3	3	3	3.5	4	5	5	5	6	
,	Р	M4螺孔 深度10		M5螺孔	深度12		M12螺孔 深度25	M16螺孔	,深度32	M20螺孔 深度40	